

Standard Product Specifications

Materials:

Steel Housing

Finish:

Powder Coated

Lens:

Acrylic Top and Bottom

LED:

Integrated LED Array

Listing:

Damp List to Meet UL 1598 Standard

Driver Info:

120V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

WBUD2 - 24.25”L x 3”H x 7”E

WBUD3 - 36.25”L x 3”H x 7”E

WBUD4 - 48.25”L x 3”H x 7”E



MODEL	FINISH	WATTAGE	KELVIN	LENS	OPTIONS
Model WBUD2 WBUD3 WBUD4	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage (2') LED36 - 36W LED 3600 Lms Wattage (3') LED45 - 45W LED 4500 Lms Wattage (4') LED64 - 64W LED 6400 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Lens CPA - Clear Prismatic Acrylic WA - White Acrylic	Options DV - 120/277 Dual Volt DIM - 0-10V Dimmable EM5 - 500 Lm Emergency EM12 - 1200 Lm Emergency P/C - Pull Chain